

MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT/MANUFACTURER'S IDENTITY

PRODUCT NAME: Paramount

PRODUCT I.D. NUMBER (PIN): N.A.

H.M.I.S.

PRODUCT NUMBER: P
PRODUCT USE: Floor finish.

WHMIS CLASS: D2B
DOT HAZARD CLASS:
Non-Hazardous

| | | |
|----------|-----------------------------|--|
| 1 | HEALTH | HAZARD RATING 4=Extreme 3=High 2=Moderate 1=Slight 0=Insignificant |
| 0 | FIRE | |
| 0 | REACTIVITY | |
| B | MAXIMUM PERSONAL PROTECTION | |

COMPANY:
TOWER INDUSTRIES, INC.
3004 SOUTH 96TH STREET
LAKEWOOD, WA 98499

DOT SHIPPING NAME:
N.A.

EMERGENCY PHONE: 253-581-2323

A=Goggles, B=Goggles & Gloves, C=Goggles, Gloves & Apron

ABBREVIATION KEY: N.A. = Not Applicable, N.E. = Not Established, N.D. = Not Determined

SECTION 2 - HAZARDOUS INGREDIENTS INFORMATION

| HAZARDOUS CHEMICAL IDENTITY | CAS NO. | % | PEL | TLV | LD50 | LC50 |
|-------------------------------------|----------------|----------|------------|------------|-------------|-------------|
| Water | 7732-18-5 | 40-70 | N.E. | N.E. | N.D. | N.D. |
| Diethylene glycol monoethyl ether | 111-90-0 | 3 | N.E. | N.E. | 5.4g/kg | N.D. |
| Dipropylene glycol monomethyl ether | 34590-94-8 | 1-5 | 100ppm | 100ppm | 7g/kg | N.D. |
| Tributoxyethyl phosphate | 78-51-3 | 1-5 | N.E. | N.E. | 9.49g/kg | 30mg/l |
| Acrylic emulsion polymer | N.A. | 40-70 | N.E. | N.E. | >5g/kg | N.D. |

This mixture contains 3% Diethylene glycol monoethyl ether which is subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR, Part 372.

SECTION 3 - PHYSICAL DATA

| | | | |
|--------------------------------------|-------------------------------------|---|--|
| Color: Milky | Boiling Point: 212°F 100°C | Vapor Pressure: <30 mm of Hg | pH: 8.1 - 8.3 |
| Odor: Bland | Freezing Point: 32°F 0°C | Vapor Density (Air=1): <1 | 1% pH: N.A. |
| Physical State: Liquid | Water/Oil Distribution: N.E. | Evaporation Rate (Water=1): N.E. | Specific Gravity: 1.03 gm/ml |
| Solubility in Water: Miscible | Odor Threshold: N.E. | VOC Content: 4.6% | Weight per Gallon: 8.60 lbs./gal. |

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

| | | |
|--|---------------------------------------|--|
| Flash Point and Method: N.A. | Autoignition Temperature: N.A. | Extinguishing Media: Use dry chemical or CO2. |
| Flammable Limits: N.A. | LEL: N.A. UEL: N.A. | Special Fire Fighting Procedures: None. |
| Hazardous Combustion Products: N.A. | | Unusual Fire and Explosion Hazards: None. |

SECTION 5 - REACTIVITY DATA

| | |
|--|--|
| Chemical Stability: Stable. | Hazardous Decomposition of By-Products: None known. |
| Incompatibility (Materials to Avoid): None known. | Hazardous Polymerization: Will not occur. |

SECTION 6 - TOXICOLOGICAL PROPERTIES

| | |
|------------------------------------|---|
| Routes of Entry: Ingestion. | Toxicologically Synergistic Products: None known. |
| Sensitization: No. | Medical Conditions Aggravated by Exposure: None known. |

EFFECTS OF OVEREXPOSURE (Acute and/or Chronic):

| | |
|---|--|
| Eyes: Direct contact may cause irritation. | Carcinogenicity: NO carcinogenic effect. |
| Skin: Prolonged or repeated contact may cause irritation. | Mutagenicity: NO mutagenic effect. |
| Ingestion: May cause gastrointestinal irritation, nausea, diarrhea. | Teratogenicity: NO teratogenic effect. |
| Inhalation: Prolonged exposure in poorly ventilated area may cause respiratory irritation. | Reproductive Toxicity: NO reproductive toxicity effect. |

SECTION 7 - PREVENTATIVE AND CONTROL MEASURES

| | |
|---|--|
| Respiratory Protection: None normally required with adequate room ventilation. | Ventilation: Local Exhaust: N.A. Mechanical: N.A. |
| Protective Gloves: Rubber to protect sensitive skin. | Eye Protection: As required to prevent splashing into eyes. |
| Protective Clothing and Equipment: As needed to prevent wetting of clothing. | Work and Hygienic Practices: Wash thoroughly after handling. |
| Storage Requirements: Store in cool, dry area. Follow good housekeeping practices. | Other Requirements: Keep out of the reach of children. |

Steps To Be Taken If Material Is Spilled Or Released: Collect and reuse if possible. Flush to sewer with large quantities of water if permitted by regulatory authorities or absorb on inert material (sand, clay, etc.) and place into container for proper disposal. Do not allow runoff into public waterways.

Waste Disposal: Dispose of as permitted by all federal, provincial, state and local regulatory authorities.

SECTION 8 - EMERGENCY FIRST AID PROCEDURES

FIRST AID - NOTES TO PHYSICIAN:

Eyes: Flush with large amount of water for 15 minutes holding eyelids open.

Skin: Wash with mild soap and water.

Ingestion: Give 2-3 large glasses of water. Seek medical attention.

Inhalation: Remove to fresh air and rest. In all cases, if symptoms persist, seek medical attention.

Note to Physician: No additional information.

SECTION 9 - PREPARATION INFORMATION

Prepared By: Regulatory Affairs Department

Phone: 253-581-2323

Date of Preparation: November, 1998